



Koryto ściekowe z rusztem
żeliwnym D400 szer. 40 cm

UMIĘJSCOWIENIE KRAWĘŻNIKA
WYSTAJĄCEGO (OK 30 M)

Luk	R= 250,00
	g[g]= 4,6296
	L= 18,18
	T= 9,09
	B= 0,17
	X(N)= 5586078,01
	Y(E)= 6464181,73

Luk	R= 200,00
	g[g]= 7,8642
	L= 24,71
	T= 12,37
	B= 0,38
	X(N)= 5586120,04
	Y(E)= 6464144,79

Luk	R= 500,00
	g[g]= 1,6156
	L= 12,69
	T= 6,34
	B= 0,04
	X(N)= 5586174,17
	Y(E)= 6464083,84

0+805,00
179.9743°

PLK 0+759,30

PLK 0+746,61

LK 0+683,80

PLK 0+559,10

PLK 0+624,61

R250.00

R500.00

254/1

253/6

253/5

252/2

252/2

250/2

250/2

249/1

249/2

251/2

251/4

251/6

251/8

251/10

251/12

251/14

251/16

251/18

251/20

251/22

251/24

251/26

251/28

251/30

251/32

251/34

251/36

251/38

251/40

251/42

251/44

251/46

251/48

251/50

251/52

251/54

251/56

251/58

251/60

251/62

251/64

251/66

251/68

251/70

251/72

251/74

251/76

251/78

251/80

251/82

251/84

251/86

251/88

251/90

251/92

251/94

251/96

251/98

251/100